



# ULTRABOARD 1913

## Asphaltic Protection Board

### PRODUCT DATA INFORMATION

---

#### DESCRIPTION:

Ultraboard 1913 is a semi-flexible asphaltic board. It is composed of an inner core consisting of asphalt, plasticizers and mineral fillers, sandwiched between two outside layers of asphalt impregnated fiber glass mat.

#### USES:

Ultraboard 1913 is constructed for use as a protective layer for waterproofing/roofing membranes. The tough, durable nature of the product makes it capable of withstanding the shock and impact of rugged backfilling, construction traffic, as well as on-site foot traffic. **Used in conjunction with Ultraseal 3750 MTO Bridge Deck Membrane as a protective layer in the waterproofing of concrete bridge decks, where asphalt hot-mix paving is installed over a layer of the board.**

#### CONFORMS TO:

Ministry of Transportation Ontario, Canada – Designated Sources List.

#### PACKAGING:

- 4,000 ft<sup>2</sup> / skid – 200 sheets

---

#### PHYSICAL PROPERTIES:

<i>Thickness:</i>	1/8" (3.2mm)
<i>Size:</i>	48" x 60" (1220 mm x 1524 mm) -- additional sizes available by request --
<i>Weight:</i>	87 lb / 100 ft <sup>2</sup>
<i>Packaging:</i>	200 sheets / skid (4,000 ft <sup>2</sup> )
<i>Weight:</i>	3384 lbs (1534 Kg) / skid

*The physical and chemical properties are typical average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations.*

---

**Disclaimer** Ultraseal Waterproofing and Sealant Technologies Inc. believes that the information contained herein is an accurate description of and uses of the product, but it is the buyers and users responsibility to determine and thoroughly confirm fitness and compatibility for use and to determine performance, efficacy, and safety.

5309 Maingate Dr. Mississauga, Ontario Canada L4W 1G6  
905-629-2209 / Fax: 905-629-3761 / Toll Free: 888-385-8721  
[www.ultrasealproducts.com](http://www.ultrasealproducts.com)



Effective Jan. 2002